

Epicuro Graffiti & Paint Remover

HEAVY DUTY WATER-BASED GRAFFITI AND PAINT REMOVER

PRODUCT DESCRIPTION

Epicuro Graffiti & Paint Remover is a high-performance paint remover capable of removing graffiti, sealers, and coatings safely and effectively without damaging the underlying surface.

Epicuro Graffiti & Paint Remover is effective at removing a wide range of finishes, including paint & varnish, stains & lacquer, graffiti, and adhesive residues. It is suitable for use on a wide variety of surfaces, including wood, metal, brick, stone, and fibreglass.

Epicuro Graffiti & Paint Remover is water based, low-VOC, non-flammable, non-corrosive, and non-ozone depleting. It is fast acting, eco-friendly and suitable for both internal and external use,

Epicuro Graffiti & Paint Remover is safe and easy-to-use, making it an excellent methylene chloride replacement.

Epicuro Hydrophobic Protection gives effective and durable protection for surfaces cleaned with Epicuro Graffiti & Paint Remover, offering increased protection for areas prone to repeated graffiti attacks.

Visit www.epicuro.co.uk to find out more.

PERFORMANCE

Epicuro Graffiti & Paint Remover is a powerful, penetrating paint stripper that works on a wide variety of surfaces and finishes.

CONSUMPTION

1-3m² per litre.

Coverage will depend on the type of substrate and the coating being removed.

ADVANTAGES & CHARACTERISTICS

- Strips paint, varnish, artex, stains and lacquers.
- Suitable for use on wood, metal, brick, stone, and fibreglass.
- Removes ALL graffiti.
- Water based, non-flammable, safe to handle and store.
- Non-corrosive, non-ozone depleting.
- Eco friendly and low VOC.
- Suitable for internal and external use.

STORAGE

If kept in original unopened container, **Epicuro Graffiti & Paint Remover** can be stored for 2 years in a cool and dry place, protected from direct sunlight.

PACKAGING

5 & 20 Litre containers.

INSTRUCTIONS FOR USE

SURFACE PREPARATION:

- Ensure surface is free from loose dirt, moss, and other debris.
- Test the product on target area before wide scale use, especially if the surface material is unknown.
- Protect adjoining areas not intended to be cleaned from overspray or spillage.

APPLICATION:

- Ensure surfaces to be stripped are dry.
- Apply **Epicuro Graffiti & Paint Remover** generously and evenly over the surface, by brush or low-pressure sprayer.
- Do not brush out.
- Leave the product to penetrate the surface for the required time.

FIND OUT MORE ABOUT EPICURO AT WWW.EPICURO.CO.UK

Finish	Dwell Time
Graffiti	5min – 4hrs
Varnish	15 - 60min
Paint	10 - 60min
Two pack varnish	30min - 2hrs
Heavy, multi-layered paint	90min – 12hrs
Artex	1 – 4 hrs

- If removing multiple layers of paint or varnish, leave for 2 hours and apply a second coat.
- After product has penetrated the surface, scrape off with suitable scrapers, leaving the surface as clean as possible.
- Rinse clean with cold water and stainless steel sourser and leave to dry. **Do not use steel wool - stainless steel only.**
- **Do not let the product dry out**, if left overnight cover with plastic (e.g. cling film) to avoid drying out.

CLEANING EQUIPMENT:

- Clean tools and equipment using clean soapy water, immediately following completion of work.

RECOMMENDATIONS

Epicuro Graffiti & Paint Remover works differently from traditional solutions, it must be left in place to work from the bottom up. This helps to avoid repeated scraping and reapplication. It is therefore more economical in application but requires a change in technique.

HEALTH & SAFETY

See separate Health & Safety Data Sheet (MSDS) for full and safety instructions.

- **Eye protection:** wear protective goggles. Ensure eye bath is to hand.
- **Hand protection:** Wear protective gloves.
- **Skin protection:** Wear protective overalls.
- **In the event of ingestion:** do not induce vomiting. Contact a doctor or a specialist.
- **Respiratory protection:** Under normal conditions of use, where adequate

ventilation is available, no special respiratory protection equipment is needed.

Where required, product users are responsible for preparing their own COSHH Assessments based on the Material Safety Data Sheets (MSDS) provided by Epicuro for its products.

KEEP OUT OF THE REACH OF CHILDREN

TECHNICAL DATA

Physical state at 20°C	: Liquid
Colour	: Off-white
Odour	: Barely Perceptible
PH	: 4/4.5
Specific Gravity	: 1.01
Coverage	: 1-3m ² per litre
Shelf-life	: 24 months from DOM

SHELF LIFE

24 months following the production date, when kept in original unopened container.

APPROVED APPLICATOR SCHEME

Approved Applicator training in product 'technology and application' is provided by Epicuro Protective Materials Ltd.

TECHNICAL ASSISTANCE

Epicuro Protective Materials Ltd

54 Oxford Road, Denham, Uxbridge, UB9 4DN

+44 (0) 20 7125 0071

Info@epicuro.co.uk

www.epicuro.co.uk

Important: The content of this documentation is based on our experience of the product. Epicuro Protective Materials Ltd guarantees the quality of its products, but expressly declines any liability in the event of failure by the user to comply with the recommendations and conditions of use of said products, notably but not exclusively in the event of incorrect application, application by unqualified personnel, use of products not compatible with Epicuro's products or bad weather conditions. For further information, refer to the safety data sheet.

Date of last update: 18/02/2022

FIND OUT MORE ABOUT EPICURO AT WWW.EPICURO.CO.UK